

ProMatrix Corporation
VPME 9.1 “VPM” Data Structures

(7/18/2006)

The data structures shown in this document use the “VPM” prefix and are primarily involved in the user interface, not data handling.

Activity

Table: **SVPMActivity**

Database: SVPM

Tags: PK (cPK), cUser (cUser), cOrigin (cOrigin), tDateTime (tDateTime)

View: **Activity_V**

Database: SVPM_V

Tags:

Filter:

Order:

View: **ActivityForm_V**

Database: SVPM_V

Tags: Date_Asc (TTOC(tDateTime,1)+cUser+cOrigin), Date_Desc (STR(1000000000000000-
VAL(TTOC(tDateTime,1)),14)+cUser+cOrigin)

Filter: cUser Like ?FindcUser AND cOrigin Like ?FindcOrigin AND tDateTime >= ?FindFrom_tMin
AND tDateTime < ?FindTo_tMax

Order:

View: **ActivityReport_V** (Read-Only)

Database: SVPM_V

Tags:

Filter:

Order: tDateTime

Field Name	Type	Width	Description/Previous Version (UACT)
cPK	C	48	
cDescription	C	50	Descr (C 50)
cOption	C	50	Option (C 50)
cOrigin	C	20	Prefix (C 3)
cUser	C	20	User (C 10)
tDateTime	T		Date_Time (T)

Admin Tools 1 (not in DD)

Table: **SVPMAAdminTools1**

Database:

Tags:

Field Name	Type	Width	Description/Previous Version (FCT1)
cID	C	10	ID (C 10)
cLabel	C	25	Label (C 25)
cRunMethod	C	30	Run_Method (C 30)
nInclude	N	1	Include (L)
nInstalled	N	1	Installed (L)

Admin Tools 2

Table: **SVPMAdminTools2**

Database: SVPM

Tags: PK (cID)

View: **AdminTools2_V**

Database: SVPM_V

Tags:

Filter:

Order:

Field Name	Type	Width	Description/Previous Version (FCT2)
cID	C	10	ID (C 10)
nStatus	N	1	Control_On (L)

Application Controls

Table: **SVPMAApplicationControls**

Database: SVPM

Tags:

Field Name	Type	Width	Description/Previous Version (DMVU)
cFiller	C	1	

Application Definition

Table: **SVPMAApplicationDefinition.APD**

Database:

Tags:

Field Name	Type	Width	Description/Previous Version (FAPD.APD)
cAddress	C	45	Address (C 45)
cAuthor	C	45	Author (C 45)
cBellFile	C	40	Bell_File (C 40)
cBuildProd	C	20	
cBuildVer	C	6	
cCity	C	20	City (C 20)
cCompany	C	45	Company (C 45)
cCurPoint	C	1	Cur_Point (C 1)
cCurSep	C	1	Cur_Sep (C 1)
cCurSymbol	C	9	Cur_Symbol (C 9)
cDateSep	C	1	Date_Sep (C 1)
cDDD_DDDS	C	48	
cDDD_V	C	80	
cDDD_VDBC	C	80	
cDDDS_V	C	80	
cDDDS_VDBC	C	80	
cDDTV_DDDS	C	48	
cDDTV_V	C	80	
cDDTV_VDBC	C	80	
cEncrChar	C	1	
cHelpFile	C	40	Help_DBF (M)
cLangID	C	3	Lang_ID (C 3)
cName	C	100	Name (C 50)
cOrigin	C	20	
cPrefix	C	3	Pjd.Prefix (C 3)
cPWChange	C	1	PW_Change (C 1)
cState	C	5	State
cVersion	C	6	Version (C 6)
cZip	C	10	Zip (C 10)
dStart	D	8	Start (D 8)
dActual	D	8	Actual (D 8)
gLogoPic	G		Logo_Pic (G)
mAppICO	M		Logo_ICO (M)
mCRCode1	M		
mCRCode2	M		
mCRCode3	M		
mFormICO	M		Form_ICO (M)
mLogoCodeG	M		
mLogoCodeM	M		
mLogoPic	M		Logo_BMP (M)
mNewDBFDir	M		DBF_Dir (M)
mNewRptDir	M		Rpt_Dir (M)
mPath	M		
mPDSURL	M		
mPosCRCode	M		

nAutoSave	N	1	AutoSave (L)
nBell	N	1	Bell (L)
nBlockSize	N	3	BlockSize (N 3.0)
nCent	N	2	Cent (N 2.0)
nCentury	N	1	Century (L)
nClear	N	1	Clear (L)
nClock	N	1	Clock (L)
nClockCol	N	3	Clock_Col (N 3.0)
nClockHrs	N	1	Clock_Hrs (N 1.0)
nClockRow	N	2	Clock_Row (N 2.0)
nClockSBar	N	1	Clock_SBar (L)
nConfirm	N	1	Confirm (L)
nCurDec	N	2	Cur_Dec (N 2.0)
nCurLeft	N	1	Cur_Left (L)
nDateFormt	N	2	Date_Formt (N 2.0)
nDebug	N	1	Debug (L)
nDevelop	N	1	Developmnt (L)
nEscape	N	1	Escape (L)
nHeading	N	1	Heading (L)
nLogo	N	1	Logo (L)
nLogoCol	N	3	Logo_Col (N 3.0)
nLogoPos	N	1	Logo_Pos (N 1.0)
nLogoRow	N	3	Logo_Row (N 3.0)
nNotify	N	1	Notify (L)
nOdometer	N	5	Odometer (N 5.0)
nPWMaxLen	N	2	PW_Max_Len (N 2.0)
nPWMinLen	N	2	PW_Min_Len (N 2.0)
nPWNoID	N	1	PW_No_ID (L)
nPWPrior	N	2	PW_Prior (N 2.0)
nPWWarning	N	2	PW_Warning (N 2.0)
nQuitConf	N	1	Quit_Conf (L)
nRefresh	N	4	Refresh (N 4.0)
nReprocess	N	5	Reprocess (N 5.0)
nRepSec	N	1	Rep_Sec (L)
nResource	N	1	Resource (L)
nRollover	N	2	Rollover (N 2.0)
nRptMgr	N	1	RptMgrType (N 1.0)
nSafety	N	1	Safety (L)
nStatusBar	N	1	Status_Bar (L)
nStrict	N	1	Strict (N 1.0)
nTypeAhead	N	3	TypeAhead (N 3.0)

Called Objects (not in DD)

Table: **SVPMCalledObjects**

Database:

Tags: PK (cCalledObj+cCObjType), Deleted (DELETED())

Field Name	Type	Width	Description/Previous Version (FCO)
cCalledObj	C	100	CalledObj (C 250)
cCObjType	C	7	CObjType (C 7)
cObj	C	100	Obj (C 250)
cObjType	C	7	ObjType (C 7)

Condition Detail

Table: **SVPMConditionDetail**

Database: SVPM

Tags: PK (cPK), cFK_Cond (cFK_Conditions), cUser (cUser), FrmRptName (cFormOrReportName),
FieldOrder (cUserID+cFormOrReportName+ STR(nFieldOrder,3,0)), Deleted (DELETED())

View: **ConditionDetail_V**

Database: SVPM_V

Tags: PK (cPK), cFK_Cond (cFK_Conditions), Order (nFieldOrder)

Filter: cPK Like ?PKValue AND cFK_Conditions Like ?ParentPKValue AND cFormOrReportName Like
?GetcFormOrReportName AND cUser Like ?GetcUser

Order: nFieldOrder

Field Name	Type	Width	Description/Previous Version (CC2)
cPK	C	48	
cFK_Conditions	C	48	
cCursorAlias	C	128	Tbl_Alias (C 254)
cFieldName	C	128	Field_Name (C 254)
cFormOrReportName	C	50	FrmRptName (C 50)
cUser	C	20	User_ID (C 10)
cValue	C	100	Value (C 100)
nFieldOrder	N	3.0	Order (N 3.0)
nOperator	N	2.0	Operator (N 2.0)

Condition Fields

Table: **SVPMConditionFields**

Database: SVPM

Tags: PK (cPK), FrmRptName (cFormOrReportName), FieldOrder
(cFormOrReportName+cCursorAlias+STR(nRelatedPagesPageNumber,2,0)+ STR(nFieldOrder,3,0)),
Deleted (DELETED())

View: **ConditionFields_V**

Database: SVPM_V

Tags: Order (cCursorAlias+STR(nFieldOrder,3,0))

Filter: cPK Like ?PKValue AND cFormOrReportName Like ?GetcFormOrReportName AND
nRelatedPagesPageNumber >= ?GetnRelatedPagesPageNumber_nMin AND
nRelatedPagesPageNumber <= ?GetnRelatedPagesPageNumber_nMax

Order: nFieldOrder

Field Name	Type	Width	Description/Previous Version (CC0)
cPK	C	48	
cCursorAlias	C	128	Tbl_Alias (C 254)
cCursorSourceDDDName	C	80	
cCursorSourceDDTVName	C	80	File_Name (C 254)
cFieldName	C	128	Field_Name (C 254)
cFormOrReportName	C	50	FrmRptName (C 50)
nAllFields	N	1.0	All_Fields (L)
nFieldOrder	N	3.0	Order (N 3.0)
nRelatedPagesPageNumber	N	2.0	RP_Page (N 2.0)

Conditions

Table: **SVPMConditions**

Database: SVPM

Tags: PK (cPK), cUser (cUser), FrmRptName (cFormOrReportName), cName (cName), Deleted (DELETED())

View: **Conditions_V**

Database: SVPM_V

Tags: PK (cPK), cName (cName)

Candidate Keys: cName+cFormOrReportName+cUser

Filter: cPK Like ?PKValue AND cFormOrReportName Like ?GetcFormOrReportName AND cUser Like ?GetcUser AND nRelatedPagesPageNumber >= ?GetnRelatedPagesPageNumber_nMin AND nRelatedPagesPageNumber <= ?GetnRelatedPagesPageNumber_nMax

Order: cName

View: **ConditionsCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cName+cFormOrReportName+cUser Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (CC1)
cPK	C	48	
cFormOrReportName	C	50	FrmRptName (C 50)
cName	C	100	Name (C 100)
cUser	C	20	User_ID (C 10)
mComments	M		Comments (M)
nRelatedPagesPageNumber	N	2.0	RP_Page (N 2.0)

Control Security – Control Group Definitions

Table: **SVPMControlGroupDefinitions**

Database: SVPM

Tags: Group_Ctrl (cGroupID+cControlID), Deleted (DELETED())

	Type	Width	Description/Previous Version (SCGD)
cControlID	C	2	ControlID (C 2)
cDescription	C	30	Descr (C 30)
cGroupID	C	12	CtrlGrpID (C 12)

Control Security - Permission Groups

Table: **SVPMControlPermissionGroups**

Database: SVPM

Tags: PK (cPK), cCode (cCode)

View: **ControlPermissionGroupsForm_V**

Database: SVPM_V

Tags: cCode (cCode)

Candidate Keys: cCode

Filter: cCode Like ?FindcCode

Order:

View: **ControlPermissionGroupsFormCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cCode Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (SCG)
cPK	C	48	
cCode	C	3	Code (C 3)
cDescription	C	30	Descr (C 30)
mComments	M		Comments (M)

Control Security - Forms

Table: **SVPMControlSecurityForms**

Database: SVPM

Tags: cFormName (cFormName)

View: **ControlSecurityForms_V** (read-only)

Database: SVPM_V

Tags:

Filter:

Order:

Field Name	Type	Width	Description/Previous Version (SFRM)
cControlGroupIDs	C	200	CtrlGrpIDs (M)
cFormCaption	C	50	FormCaptn (C 50)
cFormName	C	12	FormName (C 12)

Field Picklists

Table: **SVPMDDFP**

Database: SVPM

Tags: PK (cPK), cFK_DDF (cFK_DDF), Deleted (DELETED())

View: **DDFP_V**

Database: SVPM_V

Tags: PK (cPK), cFK_DDF (cFK_DDF), cFK_DDTV (cFK_DDTV)

Filter: cPK Like ?PKValue AND cFK_DDF Like ?ParentPKValue AND cID Like ?GetcID

Order:

Field Name	Type	Width	Description/Previous Version (DD2)
cPK	C	48	
cFK_DDF	C	48	
cFK_DDTV	C	48	Picklist T/V
cID	C	20	User defined – This ID would be entered into the new control (textbox and combobox) property cPicklistID. If the property is filled in, it is used with the GUID of the field bound to the control to find a DDFP record with matching cFK_DDF and cID values. If the property is not filled in, the GUID of the field bound to the control is used to find a DDFP record with a matching cFK_DDF value and empty cID. NOTE: We need a candidate key for cFK_DDF+cID to ensure that each combination of cFK_DDF+cID is unique. Otherwise, the user could leave cID blank on multiple records.
mAddEditForm	M		Val_Data (M)
mCaptions	M		Val_Data (M)
mFields	M		Val_Data (M)
mTags	M		Val_Data (M)
nFormWidth	N	4	Val_Data (M)
nRowsDisplayed	N	2	Val_Data (M)

Field Security - Permission Groups

Table: **SVPMFieldPermissionGroups**

Database: SVPM

Tags: PK (cPK), cCode (cCode)

View: **FieldPermissionGroupsForm_V**

Database: SVPM_V

Tags: cCode (cCode)

Candidate Keys: cCode

Filter: cCode Like ?FindcCode

Order:

View: **FieldPermissionGroupsFormCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cCode Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (SFG)
cPK	C	48	
cCode	C	3	Code (C 3)
cDescription	C	30	Descr (C 30)
mComments	M		Comments (M)

Languages

Table: **SVPMLanguages**

Database: SVPM

Tags: PK (cPK), Lang_ID (cLanguageID), Deleted (DELETED())

View: **Languages_V**

Database: SVPM_V

Tags: PK (cPK), Lang_ID (cLanguageID)

Candidate Keys: cLanguageID

Filter:

Order:

View: **Languages_Picklist_V** (read-only)

Database: SVPM_V

Tags: PK (cPK)

Filter: NOT cLanguageID == "ML"

Order:

View: **Languages_Picklist2_V** (read-only)

Database: SVPM_V

Tags: Lang_ID (cLanguageID)

Filter: cLanguageID Like ?PKValue

Order:

View: **LanguagesCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cLanguageID Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (IL)
cPK	C	48	
cCurrencyPoint	C	1	Cur_Point (C 1)
cCurrencySeparator	C	1	Cur_Sep (C 1)
cCurrencySymbol	C	9	Cur_Symbol (C 9)
cDateSeparator	C	1	Date_Sep (C 1)
cDescription	C	50	Lang_Desc (C 50)
cLanguageID	C	3	Lang_ID (C 3)
mComments	M		Lang_Comm (M)
nAddConstant	N	1	Add_Const (L)
nAddCaption	N	1	Add_Cap (L)
nAddControlSource	N	1	Add_CS (L)
nAddDownPicture	N	1	Add_DnPic (L)
nAddDragIcon	N	1	Add_DrgIco (L)
nAddFont	N	1	Add_Font (L)
nAddIcon	N	1	Add_Icon (L)
nAddInputMask	N	1	Add_InpMsk (L)
nAddMenu	N	1	Add_Menu (L)
nAddPicture	N	1	Add_Pic (L)
nAddRecordSource	N	1	Add_RecSrc (L)
nAddReportFont	N	1	Add_Rpt (L)
nAddRowSource	N	1	Add_RowSrc (L)

nAddStatusBarText	N	1	Add_SBTxt (L)
nAddToolTipText	N	1	Add_TTTxt (L)
nCurrencyDecimals	N	2	Cur_Dec (N 2.0)
nCurrencySymbolLeft	N	1	Cur_Left (L)
nDateFormat	N	2	Date_Formt (N 2.0)
nTranslateCaptionProperty	N	1	Trn_Cap (L)
nTranslateControlSourceProperty	N	1	Trn_CS (L)
nTranslateDownPictureProperty	N	1	Trn_DnPic (L)
nTranslateDragIconProperty	N	1	Trn_DrgIco (L)
nTranslateFontProperty	N	1	Trn_Font (L)
nTranslateIconProperty	N	1	Trn_Icon (L)
nTranslateInputMaskProperty	N	1	Trn_InpMsk (L)
nTranslateMessages	N	1	Trn_Mess (L)
nTranslatePictureProperty	N	1	Trn_Pic (L)
nTranslateRecordSourceProperty	N	1	Trn_RecSrc (L)
nTranslateReportFonts	N	1	Trn_Rpt (L)
nTranslateRowSourceProperty	N	1	Trn_RowSrc (L)
nTranslateStatusBarTextProperty	N	1	Trn_SBTxt (L)
nTranslateStrings	N	1	Trn_Str (L)
nTranslateToolTipTextProperty	N	1	Trn_TTTxt (L)

Menu Security – Menu Options

Table: **SVPMMenuOptions**

Database: SVPM

Tags:

View: **MenuOptions_V** (read-only)

Database: SVPM_V

Tags:

Filter:

Order:

Field Name	Type	Width	Description/Previous Version (SMNU)
cDescription	C	50	Option (C 50)
cID	C	10	
cParentID	C	10	
cMenuIDNumber	C	3	ID_Number (C 3)
cMenuOptionNumber	C	3	Opt_Number (C 3)

Menu Security - Permission Groups

Table: **SVPMMenuPermissionGroups**

Database: SVPM

Tags: PK (cPK), cCode (cCode)

View: **MenuPermissionGroupsForm_V**

Database: SVPM_V

Tags: cCode (cCode)

Candidate Keys: cCode

Filter: cCode Like ?FindcCode

Order:

View: **MenuPermissionGroupsFormCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cCode Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (SMG)
cPK	C	48	
cCode	C	3	Code (C 3)
cDescription	C	30	Descr (C 30)
mComments	M		Comments (M)

Menus (not in DD)

Table: **SVPMMenus**

Database:

Tags: PK (cName), cDesc (cDesc), Deleted (DELETED())

Field Name	Type	Width	Description/Previous Version (FMNU)
cDesc	C	40	Desc (C 40)
cName	C	8	ID (C 8)
cOBName	C	8	Obj_Bldr (C 8)
mCurMenu	M		Cur_Menu (M)
mLocation	M		Location (M)
nMenuNo	N	3	ID_Number (N 3.0)

Messages

Table: **SVPMMessages**

Database: SVPM

Tags: PK (cPK), cMessageID (cMessageID), Deleted (DELETED()), UMessID (UPPER(cMessageID))

View: **Messages_V**

Database: SVPM_V

Tags: PK (cPK), cMessageID (UPPER(cMessageID))

Candidate Keys: cMessageID

Filter:

Order:

View: **MessagesCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cMessageID Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (UMES)
cPK	C	48	
cBellFile	C	40	Bell_File (C 40)
cFontName	C	40	Font_Name (C 40)
cFontStyle	C	2	Font_Style (C 2)
cFormCaption	C	100	Form_Cap (C 100)
cImageFile	C	40	Image_File (C 40)
cMessageID	C	50	Mess_ID (C 50)
mButtons	M		Buttons (M)
mComments	M		Mess_Comm (M)
mText	M		Mess_Text (M)
nButtonSelection	N	1	Button_Sel (N 1.0)
nCancelButton	N	1	Button_Can (N 1.0)
nDefaultButton	N	1	Button_Def (N 1.0)
nDisplayImage	N	1	Disp_Image (L)
nExpression	N	1	Mess_Expr (L)
nFontSize	N	2	Font_Size (N 2.0)
nNoWait	N	1	Wt_NoWait (L)
nPictureSelection	N	1	Image_Sel (N 1.0)
nSoundBell	N	1	Sound_Bell (L)
nType	N	1	Mess_Type (N 1.0)
nWaitTimeout	N	6.2	Wt_Timeout (N 6.2)

Message Translations

Table: **SVPMMMessageTranslations**

Database: SVPM

Tags: PK (cPK), FKL_FKM (cFK_Languages+cFK_Messages), Deleted (DELETED())

View: **MessageTranslations_V**

Database: SVPM_V

Tags: PK (cPK), FK_Lang (cFK_Languages), FK_Mess (cFK_Messages), Lang_Child
(cFK_Languages+UPPER(cMessageID)), Lang_Mess (cLanguageID+UPPER(cMessageID)),
Mess_Child (cFK_Messages+cLanguageID), Mess_Lang (UPPER(cMessageID)+cLanguageID)

Candidate Keys: cFK_Languages+cFK_Messages

Filter:

Order:

View: **MessageTranslationsCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cFK_Languages+cFK_Messages Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (IM)
cPK	C	48	
cFK_Languages	C	48	
cFK_Messages	C	48	
cLanguageID	C	3	View Only – Joined from SVPMLanguages.cLanguageID
cMessageID	C	50	View Only – Joined from SVPMMessages.cMessageID
mText	M		Mess_Text (M)
nExpression	N	1	Mess_Expr (L)

Project Definition (not in DD)

Table: **SVPMProjectDefinition.PJD**

Database:

Tags:

Field Name	Type	Width	Description/Previous Version (FPJD.PJD)
cBuildEXE	C	100	Build_EXE (C 100)
cProjID	C	6	Proj_ID (C 6)
dTarget	D	8	Target (D)
mBuildData	M		Build_Data (M)
mBuildHome	M		Build_Home (M)
mBuildRpt	M		Build_Rpts (M)
mBuildSub1	M		Build_Sub1 (M)
mBuildSub2	M		Build_Sub2 (M)
mBuildSub3	M		Build_Sub3 (M)
mComments	M		Comments (M)
mCtrlsLib	M		Ctrls_Lib (M)
mDataDir	M		DBF_Dir (M)
mFormDir	M		Scrn_Dir (M)
mHomeDir	M		Home_Dir (M)
mMenuDir	M		Menu_Dir (M)
mPLibDir	M		PLib_Dir (M)
mPrgDir	M		Prg_Dir (M)
mRptDir	M		Rpt_Dir (M)
mTeam	M		Team (M)
mUpdHome	M		Upd_Home (M)
nLeftLbIs	N	1	Left_LbIs (L)
nProjSec	N	1	Proj_Sec (L)

Reports

Table: **SVPMReports**

Database: SVPM

Tags: PK (cPK), Descr (cDescription), RptLblName (cReportOrLabelName), cType (cType), Deleted (DELETED())

View: **Reports_V**

Database: SVPM_V

Tags:

Candidate Keys: cReportOrLabelName+cType

Filter: cReportOrLabelName Like ?GetcReportOrLabelName AND cType Like ?GetcType

Order:

View: **ReportsCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cReportOrLabelName+cType Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (URPT)
cPK	C	48	
cDescription	C	40	Descr (C 40)
cReportOrLabelName	C	128	ID (C 250)
cType	C	6	Type (C 6)
nDisplay	N	1	Display (L)
nTranslateFonts	N	1	Trn_Rpt (L)
nUseReportSetupFor	N	1	Prt_Sel_F (L)
nUseReportSetupForm	N	1	Prt_Sel (L)
nUseReportSetupOrder	N	1	Prt_Sel_O (L)
nUseReportSetupWhile	N	1	Prt_Sel_W (L)
mLocation	M		Location (M)

Security Data

Table: **SVPMSecurityData**

Database: SVPM

Tags: PK (cData)

View: **SecurityData_V**

Database: SVPM_V

Tags: ControlSec (SUBSTR(cData,5,36)), FieldSec (SUBSTR(cData,5,52)), MenuSec (SUBSTR(cData,5,28))

Filter:

Order:

Field Name	Type	Width	Description/Previous Version (SEC)
cData	C	57	Encrypted (C 30)

cData field contents:

Security Type	Starting Position	Width	Content Description
Control	1	4	Check Sum
	5	1	"C" (Control Security)
	6	1	"U" (User) or "G" (Group)
	7	20	User ID or Control Permission Group Code
	27	12	Form Name
	39	2	Control ID
Field	41	17	SPACE(17)
	1	4	Check Sum
	5	1	"F" (Field Security)
	6	48	Field ID (DDF PK)
	54	3	Field Permission Group Code
Menu	57	1	"N" (No Display) or "D" (Display Only)
	1	4	Check Sum
	5	1	"M" (Menu Security)
	6	1	"U" (User) or "G" (Group)
	7	20	User ID or Menu Permission Group Code
	27	3	Menu Number
	30	3	Menu Option Number
33	25	SPACE(25)	

Strings

Table: **SVPMStrings**

Database: SVPM

Tags: PK (cPK), Str_Use (UPPER(cStringID)+cUseID), Deleted (DELETED())

View: **Strings_V**

Database: SVPM_V

Tags: PK (cPK), Str_Use (UPPER(cStringID)+cUseID), Use_ID (cUseID+UPPER(cStringID))

Candidate Keys: cStringID+cUseID

Filter:

Order:

View: **StringsCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cStringID+cUseID Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (ISTR)
cPK	C	48	
cStringID	C	50	Str_ID (C 50)
cUseID	C	2	Use_ID (C 2)
mComments	M		Str_Comm (M)
mLocation	M		Str_Loc (M)

String Translations

Table: **SVPMStringTranslations**

Database: SVPM

Tags: PK (cPK), FKL_FKS (cFK_Languages+cFK_Strings), Deleted (DELETED())

View: **StringTranslations_V**

Database: SVPM_V

Tags: PK (cPK), FK_Lang (cFK_Languages), FK_Str (cFK_Strings), Lang_Child

(cFK_Languages+UPPER(cStringID)+cUseID), Lang_Str

(cLanguageID+UPPER(cStringID)+cUseID), Str_Child (cFK_Strings+cLanguageID), Str_Use

(UPPER(cStringID)+cUseID+cLanguageID), Use_Str (cUseID+UPPER(cStringID)+cLanguageID)

Candidate Keys: cFK_Languages+cFK_Strings

Filter:

Order:

View: **StringTranslationsCK_V** (read-only)

Database: SVPM_V

Tags:

Filter: cFK_Languages+cFK_Strings Like ?CandidateValue

Order:

Field Name	Type	Width	Description/Previous Version (IS)
cPK	C	48	
cFK_Languages	C	48	
cFK_Strings	C	48	
cLanguageID	C	3	View Only – Joined from SVPMLanguages.cLanguageID
cStringID	C	50	View Only – Joined from SVPMStrings.cStringID
cUseID	C	2	View Only – Joined from SVPMStrings.cUseID
mText	M		Str_Text (M)
nExpression	N	1	Str_Expr (L)

System Controls

Table: **SVPMSystemControls**

Database: SVPM

Tags:

Field Name	Type	Width	Description/Previous Version (DMV)
cFiller	C	1	

Toolbar Controls

Table: **SVPMToolbarControls**

Database: SVPM

Tags: cID (cID)

View: **ToolbarControls_V**

Database: SVPM_V

Tags: cID (cID)

Filter:

Order:

Field Name	Type	Width	Description/Previous Version
cID	C	30	
cDescription	C	80	
cCaption	C	80	
cCaption_Alt	C	80	
cPicture	C	50	
cPicture_Alt	C	50	
cToolTipText	C	80	
cToolTipText_Alt	C	80	
nAutoSize	N	1	
nCaptionAlignment	N	1	
nControlHeight	N	3	
nControlWidth	N	3	
nPictureMargin	N	2	
nPicturePosition	N	2	
nPictureSpacing	N	2	